

SAYFA[®]

ANCHOR POINT STROP

SAYFA[®]
PROTECT

1300 301 755
SAYFA.COM.AU

PRODUCT
SPECIFICATION

PRODUCT CODE
AP 115

DESCRIPTION
ANCHOR POINT STROP
WITH QUICKLINK

PROPRIETARY ANCHOR POINT EXTENSION FOR SAFE WORK AT ACCESS POINT

- Fall arrest rated - 15kN
- PVC coated stainless steel cable and end terminals
- Batch number identification with internal tracer ribbon
- Includes fall arrest rated quicklink

PRODUCT
BROCHURE



TECHNICAL SPECIFICATION

SYSTEM CODE SPECIFICATION SUMMARY

AP115 ANCHOR POINT STROP WITH FALL ARREST RATED QUICKLINK
System design, supply, layout, installation and certification by a Sayfa accredited installer, as per the manufacturer's installation instructions and current standards.

TECHNICAL DATA

RATING

- Fall arrest only - 15kN

MATERIALS

- Anchor strop - PVC coated stainless steel (6mm cable)
- Eyelets - PVC coated stainless steel

DIMENSIONS

- Strop eyelet diameter - 22mm
- Quicklink - 8mm screw gate type (18mm gate opening)
- Strop lengths - 1000, 1500, 2000, 3000mm (eye to eye)
- AP115.1000 - 1000mm
- AP115.1500 - 1500mm
- AP115.2000 - 2000mm
- AP115.3000 - 3000mm



PVC COATED



BATCH NUMBER IDENTIFICATION

COMPLIANCE

The AP115 Anchor Point Strop with Quicklink is designed and manufactured in accordance with requirements of Australian Standards AS/NZS 1891.4:2009 and AS/NZS 5532:2013.

TESTING

Testing and performance based on AS1891.4:2009.
- Dynamic load test - 15kN
- Static load test - 15kN

PRODUCT WARRANTY

3 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

INSPECTION AND MAINTENANCE

This device requires periodic inspection and maintenance by a qualified safety inspector.
(Refer instruction manual.)

IMPORTANT NOTE

Not to be used for rope access

Designed and manufactured by Sayfa Group. For all technical assistance contact Sayfa Group. SAYFAGROUP-1.3.2016

DISCLAIMER

All product specifications and technical descriptions, recommendations and other information provided, are given as general guidance and advice, and are to be read in conjunction with Sayfa Group installation instructions and any other data available and applicable to each particular standard product or system. Use of such data is however the user's sole responsibility, taking into account the intended application and actual conditions existing on the particular worksite. Consequent selection of the right product for any particular use, remains the user's ultimate responsibility. Sayfa Group is therefore not obligated or liable for any direct or indirect, incidental or consequential damages, losses or expenses in connection with, or by reason of the suitability and use of or otherwise, any product or system for any purpose. Implied warranties of merchantability or fitness for any particular purpose, are specifically excluded.

All Sayfa Group products must be installed and used by competent personnel trained in the selection, safe use and maintenance of fall arrest systems and equipment by a registered training organisation (RTO). Installation not in accordance with Sayfa Group requirements or the use of non Sayfa Group components will void all certification and warranties.

Suitability of support structure and design layout of system is the responsibility of the installer and should be verified by a structural engineer or a site specific live load test done to ensure conformance. Maintenance and usage of the system in accordance with Sayfa Group requirements is the responsibility of the owner or manager of the workplace.

