


DISCLAIMER

All product specifications and technical descriptions, recommendations and other information provided in this drawing, are given as general guidance and advice, and are to be read in conjunction with Sayfa Systems installation criteria. Sayfa can not be held responsible for any information herein.



ST570 - Step Ladder  
for access under roof hatches

NOTES

The ALTO Step Ladder Systems complies with AS1657:2013 when installed as per the instructions detailed. These drawings and Instructions must be read in conjunction with the Australian Standards Criteria.

1. Distance between handrails 550mm - 750mm (Std ladder width - 600mm)
2. Hand clearance - Min 50mm between the edge of any handrail and adjacent structure.
3. There shall be 200mm foot clearance from the front of the tread.
3. All step ladders are designed for 150kg.
4. There must be 1000mm Clearance from the front nosing of the step (Head Room Clearance)
5. The vertical distance between landings shall not exceed 6m. if it exceeds 6m, there shall be a change in direction by 180° or where this is not possible it shall have a landing, midway of not less than 1500mm long.
6. There shall be a landing from the front of the ladder of min 900mm long (600mm wide)
7. Where a person could fall more than 6m, the step ladder must be fitted with a side screen or a ladder cage.
8. Guardrail Protection is required around any opening where there is a fall of more than 2000mm. Extension stiles is an 'optional extra'.